



CHIEFS PLATINUM WASH

Chiefs Australia Product Information Training Chiefs Platinum Wash

The above video needs to be watched in full for you to progress to the product information tutorial

Chiefs Platinum Wash (Available in 5L, 20L, 200L and 1000L)

Chiefs Platinum Wash is your ultimate bling truck cleaning tool and is specifically designed to touchlessly clean vehicles that have polished aluminium tanks, bull bars, roll bars, side steps and rims, without streaking the aluminium. This product is manufactured in Australia for Australian conditions and is safe on all paintwork as it is caustic free, giving you that fleet wash clean.

Mixing Ratio

Suttner ST73 Foam Lance:

100% soap on setting 1 (2-2.5%).

LS-3 (Formally known as PA Foamer):

200ml soap to 800ml water. The regulator should be in the full minus position and then adjust if necessary. This equates to 2%.

Should you have any other brand foam lance, based on a 1L chemical bottle, please mix between 100–200ml of Active Diamond to 900-800ml of water. Please note that this is a guide only as it is dependent on the type of foam lance and the pressure washer's pressure and flow settings.

This product can also be used through Suttner Downstream injectors, ST160 / ST164 and the Chiefs InjectaChem:

Dousing restrictor 0.7 (1%) to 1.0 (2.5%).

Application Instructions

It is strongly advised to test Platinum Wash on a small inconspicuous area before use.

Apply a thin layer of foam over a dry vehicle and allow to dwell for around 1 minute.



P: 07 5493 8868

A: 3/6 Textile Avenue Warana QLD 4575

chiefsaustralia.com

ABN: 23 604 979 688



KENOTEK





Using high pressure water start cleaning from the bottom to the top or backwards into fresh soap covering all areas. (See video in "How to Videos").

Rinse any excess soap from the top to the bottom.

This product is safe on all paints, stainless steel and chrome.

Care should be taken if using on ceramic coating, please refer to manufacturers guidelines BEFORE applying the product

Avoid letting the product dry on the vehicle. Should this happen please re-foam to reactivate the soap and wash off as per the above instructions.

Avoid applying the soap on hot surfaces. This is due to the foam consisting largely of water and on contact with a hot surface, the water in the foam will evaporate leaving the product only adhered to the surface. Should this happen, re-foam to reactivate the soap and wash off as per the above instructions.

Due to Australian weather conditions, if application of the product in hot conditions cannot be avoided, it is suggested to apply in sections using the above application technique.

Technical Specifications

Product codes

5L – 124090

20L – 124091

200L – 124100

1000L – 124129

Colour: Brown

Foam intensity – Strong

pH 100%: 10.5-11.5

Biodegradability: The material is readily biodegradable

Specific gravity: 1,0kg/L ± 1%

Safe Handling and Storage



P: 07 5493 8868

A: 3/6 Textile Avenue Warana QLD 4575

chiefsaustralia.com

ABN: 23 604 979 688



The complete safety instructions of the product can be found on the material safety data sheet. Keep the product in the original and closed packaging and protect from extreme temperatures and direct sunlight.

Personal Protective Equipment

Please ensure using appropriate PPE equipment when using any chemicals which should include eye / face protection, gloves, ear protection when using pressure washers or air compressors, appropriate face masks or respirators when misting products or working in enclosed spaces. Always check the products safety data sheets before use.



P: 07 5493 8868

A: 3/6 Textile Avenue Warana QLD 4575

chiefsaustralia.com

ABN: 23 604 979 688



KENOTEK

