



ABN 23 604 979 688 Nerta QLD Pty Ltd t/as Chiefs Australia

ST-167 EASYFOAM 365+ BYPASS INJECTOR



Product Description:

The Stainless Steel injectors are able to open two cross section areas (50 mm 2 each) in order to guarantee a smooth use without drop in pressure when washing/rinsing. This ensures that the injector can be permanently kept in the high pressure line, even when large water quantities are used.

A lever makes it possible to change from the cleaning and rinsing mode into injector operation. When using the cleaning mode, there are two bore holes guiding the high pressure water parallel to the injector (bypass mode).

In combination with a foam lance (ST-72, ST-74 or ST-75), an adjustable or a triple nozzle the easyfoam365+ injector ST-167 can suck in chemicals by means of the integrated stainless steel check valve.

Technical Details:

Inlet	½" Female
Outlet	½" Female
Max Pressure	350 Bar
Max Temp	100°C

P: 07 5493 8868
M: 0476 350 552
A: 3/6 Textile Avenue Warana QLD 4575
E: clientsupport@chiefsaustralia.com
chiefsaustralia.com



KENOTEK



ABN 23 604 979 688 Nerta QLD Pty Ltd t/as Chiefs Australia

Product Guide cont.

Product ID	Product SKU	Injector Sizes	Diffuser Nozzle Sizes
124612	200167505	1.7	2.0
124868	200167503	1.5	1.7
125157	200167506	1.8	2.3
125222	200157504	1.6	2.0
125393	200167502	1.4	1.7
125394	200167501	1.3	1.7
125395	200167507	1.9	2.3
125396	200167508	2.0	2.8
125397	200167509	2.1	2.8
125398	200167510	2.2	2.8



P: 07 5493 8868
M: 0476 350 552
A: 3/6 Textile Avenue Warana QLD 4575
E: clientsupport@chiefsaustralia.com
chiefsaustralia.com



KENOTEK