

## ST33 HIGH PRESSURE FILTER



### PRODUCT DESCRIPTION

ST33 HIGH PRESSURE FILTER  
Bidirectional

ideal for the filtration of high pressure, rotating and sewer cleaning nozzles in case of:

- a frequent exchange of nozzles
- lengthening or shortening of hose pipes
- the assembly of stationary pipelines

complying with the highest requirements to durability of high pressure accessories

easy adaptation e.g. directly between lance and rotating nozzle or in terms of ergonomics at the inlet of the lance

integrated stainless steel filter

max. allowed working pressure of 400 bar

suitable for temperatures of up to 150 °C

flow: 40 l/min

1/4" female and male thread, bidirectionally flowing through [Click here to view on page 68 of 2020 R+M](#)

[Catalogue](#) [Click here to view on page 182 of 2020 R+M Catalogue](#) [Click here to view on page 283 of 2020 R+M Catalogue](#)

TO ORDER THIS ITEM USE PRODUCT CODE: [200033855](#)

## TECHNICAL DETAILS

max. pressure 400 bar / 6,000 psi  
max. temperature 150 °C  
thread 1/4"  
material housing brass  
material filter stainless steel  
mesh size 0,3 mm  
flow 40 l/min

## CONTACT DETAILS

G & S Penrith Ltd  
TecPro House  
Blamire Road  
Eden Business Park  
Penrith  
CA11 9FD  
T: 01768 865985