

# Chiefs Full Force Degreaser

## Product Information and Instructions

Full Force Degreaser is a heavy-duty cleaning detergent. It is a concentrated biodegradable formula suitable for engine bays, heavy machinery, and trucks.

Full Force Degreaser has excellent foaming properties, producing a thick foam that allows extra surface dwell time for thorough emulsification of grease, oil and hydraulic fluid.

**Available in 20L, 200L and 1000L.**

### Dilution and Usage

**Via Suttner Downstream Injectors ST-160/ST-167/ST-164:** Dousing restrictor between 1.5 and 2.0 (8–13.5%)

**Via Suttner ST-73 Foam Lance:** Use undiluted (neat) soap on Setting 5 (6.5–8%)

**Via other foam lances:** The dilution should be estimated to output a foam concentration of 8%—the required dilution will vary between brands. As a guide, use a 1:1 dilution ratio in the foamer bottle and set the lance regulator to the full minus position.

### Application Instructions

Apply a single, thick layer of foam over the contaminated area and allow to dwell for around 1 minute. Cold water should be used for application of the foam.

Use high-pressure water to remove emulsified grease and oil, rinsing thoroughly. Hot water may be used for washing.

### Notes

- This product is safe on all paints, stainless-steel and chrome.
- **Do not use on polished aluminium** as this product may leave a white veil or streak the aluminium.
- Care should be taken if using on ceramic coating, please refer to the vehicle manufacturer's guidelines BEFORE applying the product.
- It is recommended that you test all products on a small inconspicuous area before use.
- Avoid letting the product dry on the vehicle, should this happen please re-foam to reactivate the product and wash off as per the instructions above.
- Avoid applying the soap to hot surfaces. The dense foam consists primarily of water (a small volume of product is required for cleaning)—as such, hot surfaces will cause the water to evaporate and leave the product adhered to the surface. Should this occur, re-foam over the area to reactivate the soap and wash off as per the instructions above.
- Due to Australian weather conditions, if application of the product in hot conditions cannot be avoided the product should be applied and washed off in sections, working around the vehicle.